

TESK10

HYDRAULIC MULCHER TRINCIATRICE IDRAULICA



**WATCH IT IN ACTION
GUARDA IN AZIONE**

FEATURES

- Powerful forestry mulcher, designed for mounting on skid steer loaders.
- Fixed universal hitch.
- DF forestal rotor with fixed teeth.
- Hydraulic translation.
- Mechanically adjustable push bar.
- Manometer for working pressure control.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation and self-draining.
- Piston motor.
- Accident prevention rubber protections according to EC directives.

Upon request:

- mounting bracket, custom-made available;
- hoses.
- hydraulic push bar.

CARATTERISTICHE

- Potente trinciatrice forestale, progettata per il montaggio su minipala.
- Attacco fisso universale.
- Rotore DF a denti fissi in widia o lama o bonificata.
- Traslazione idraulica.
- Abbattirami meccanico.
- Manometro per controllo pressione di lavoro.
- Blocco valvole comprensivo di valvola prioritaria per regolazione della portata olio, antiurto (valvola di max pressione), anticavitazione e autodrenante.
- Motore a pistoni a cilindrata fissa.
- Protezioni antinfortunistiche in gomma a norma CE.

Su richiesta:

- sella di attacco, disponibile su misura;
- fornitura di tubi;
- abbattirami idraulico.

TECHNICAL INFORMATION

CARATTERISTICHE TECNICHE



Rotor
 Rotore

DF



DFHF14P
 Ø max 30 cm



DFHF15
 Ø max 25 cm



MODELLO MODEL	hp	cm/inch	LxAxH cm/inch	kg/lbs	CILINDRATA MOTORE ENGINE DISPLACEMENT	l/min - gpm	bar - psi (min-max)		
TESK1.10-160DF	70 - 120	160 63	200x100x160 79x40x63	1285 2833	45-60-80	100-130-180 28-35-48	200-350 2900-5100	1	42
TESK2.10-180DF	70 - 120	180 71	220x100x160 87x40x63	1420 3131	45-60-80	100-130-180 28-35-48	200-350 2900-5100	1	54

Hydraulic piston motor range
 Scelta motore idraulico a pistoni

CILINDRATA MOTORE ENGINE DISPLACEMENT	45	60	80
l/min gpm	100 28	130 35	180 48